

# BL0202

## 2" x 2" Surface Mount LED Back Light

- Aii** Extremely consistent light over the entire active area of illumination.
- Aii** Integral M6 nut channel for easy mounting.



### Ordering Information


Standard Product:  
Shipped Next Day  
**BL0202-660**  
Configured for use with Ai power supply  
**BL0202-66024**  
Configured for use with user supplied 24vDC Power Supply

Standard Product Variation:  
**Red & White:** Shipped Within Two Weeks  
**Blue & Infra-red:** 4 Weeks **Green:** 6 Weeks

Spectral wavelength	Optional power Compatibility	Optional Light Conditioning		
		Alternative Connector		
BL0202 -	XXX	XX	X	XXX
(blue) 470 †	IC		P	M12* (male)
(green) 520 †	IS		(Polarizer)	
(red) 660	C2			
(infra-red) 880	C3			
(white) WHI †	C5			
	24			

IC = ICS (requires 24v power supply)  
IS = ISU (requires 24v power supply)  
C2 = Ai Connector  
C3 = Pulsar 710 Connector  
C5 = Pulsar 320 Connector  
\* Available with IC, IS, and 24v options only  
† Not available with IC or 12v

### Dimensional Information



[Click for Installation Models & Drawings](#)

Cable Length: 1.5 Meter (59")

DIMENSIONS ARE IN MILLIMETERS (INCHES)

#### Standard Variation Current Specifications

	blue	green	red	infra-red	white	
@24	80	80	120	120	80	mA

#### Standard Product Information

Weight:	368 g (13 oz)
Finish:	Black Anodized
Operating Temperature:	0-60 C
Meets Specifications:	CE, RoHS
Product Lifetime:	50,000 hours