

CB0404

4" x 4" Collimated Surface Mount LED Back Light

- Aii** Greatly improves edge detection for curved surfaces
- Aii** Integrated M6 nut channel for mounting (hardware included)



Ordering Information


Standard Product:
Shipped Next Day
CB0404-WHIIC
Configured with inline
Current Source

Standard Product Variation:
Red & White: Shipped Within Two Weeks
Blue & Infra-red: 4 Weeks **Green:** 6 Weeks

	Spectral wavelength	Optional power Compatibility	Alternative Connector
CB0404 -	XXX	XX	XXX
	(blue) 470 †	IC	M12* (male)
	(green) 520 †	IS	
	(red) 660 ⊖	C2	
	(infra-red) 880 ⊖	C3	
	(white) WHI †	C5	
		24	

IC = iCS (requires 24v power supply)
IS = iSU (requires 24v power supply)
C2 = Ai Connector
C3 = Pulsar 710 Connector
C5 = Pulsar 320 Connector
* Available with IC, IS, and 24v options only
† Not available in 12v
⊖ IS option not available

Dimensional Information



Cable Length: 1.5 Meter (59")

Standard Variation Current Specifications

	blue	green	red	infra-red	white	
@24/Ai	320	320	480	480	320	mA

Standard Product Information

Weight:	626.1 g (22 oz)
Finish:	Black Anodized
Operating Temperature:	0-60 C
Meets Specifications:	CE, RoHS
Product Lifetime:	50,000 hours