



USB
VISION GEN*i*CAM



sensor information

sensor	Sony ICX618
type	1/4" progressive scan CCD
resolution	656 × 490 px
pixel size	5.6 × 5.6 μm

acquisition formats

image formats, frame rate max.	Full Frame, 656 × 490 px, max. 160,0 fps
pixel formats	Mono8 Mono12 Mono12 Packed

image pre-processing

analog controls	Gain (0 ... 29.5 dB) Offset (0 ... 1023 LSB 14 Bit)
color models	Mono

interfaces and connectors

data interface	USB 3.0, Transfer Rate 5000 Mbits/sec, Connector: USB 3.0 Micro B
process interface	JSTBM08B-SRSS-TB 8 pins

mechanical data

material	without housing
lens mount	C-mount / S-mount (adapter)
width	28,5 mm (sensor print) 48 mm (system print)
height	28,5 mm (sensor print) 48 mm (system print)
weight	≤ 30 g

electrical data

power consumption	approx. 2,6 W @ 160,0 fps
-------------------	---------------------------

environmental conditions

operating temperature	Depends on the thermal encapsulation (T _{max} = 70 °C @ Measurement Point)
humidity	10 ... 90 % (non-condensing)

digital I/Os

lines	1 input line 1 output line 2 general purpose lines
-------	--

dimension drawing

