



**USB**  
VISION GEN*i*CAM



### sensor information

sensor	Sony IMX252
type	1/1.8" progressive scan CMOS
resolution	2448 × 2048 px
exposure time	0,026 ... 60000 ms
pixel size	3.45 × 3.45 μm

### acquisition formats

image formats, frame rate max.	Full Frame, 2048 × 1536 px, max. 120,0 fps Binning 2×2, 1024 × 768 px, max. 120,0 fps Binning 2×1, 1024 × 1536 px, max. 120,0 fps Binning 1×2, 2048 × 768 px, max. 120 fps
--------------------------------	---

pixel formats	Mono8 Mono10 Mono12 Mono12 Packed
---------------	--

### image pre-processing

analog controls	Gain (0 ... 48 dB) Offset (0 ... 255 LSB 12 Bit)
-----------------	---

color models	Mono
--------------	------

### interfaces and connectors

data interface	USB 3.0, Transfer Rate 5000 Mbits/sec, Connector: USB 3.0 Micro B
process interface	M8 / 8 pins (SACC-DSI-M8FS-8CONM10-L180 SH)
power supply	via USB 3.0 interface

### mechanical data

material	zinc die casting, nickel-plated, IP 40
lens mount	C-mount
width	29 mm
height	29 mm
depth	38 mm
weight	≤ 90 g

### electrical data

power consumption	approx. 2,5 W @ 120 fps
-------------------	-------------------------

### environmental conditions

operating temperature	+5 ... +65 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

### digital I/Os

lines	1 input line 1 output line 2 general purpose lines
-------	--

### dimension drawing

