



GIG VISION **GEN<i>i</i>CAM**



sensor information

| | |
|---------------|-----------------------------|
| sensor | ON Semiconductor PYTHON1300 |
| type | 1/2" progressive scan CMOS |
| resolution | 1280 × 1024 px |
| exposure time | 0,04 ... 1000 ms |
| pixel size | 4.8 × 4.8 μm |

acquisition formats

| | |
|--------------------------------|---|
| image formats, frame rate max. | Full Frame, 1280 × 1024 px, max. 61,0 fps Binning 2×2, 640 × 512 px, max. 61,0 fps Binning 2×1, 640 × 1024 px, max. 61,0 fps Binning 1×2, 1280 × 512 px, max. 61,0 fps |
|--------------------------------|---|

| | |
|---------------|-----------------|
| pixel formats | Mono8 Mono10 |
|---------------|-----------------|

image pre-processing

| | |
|-----------------|--|
| analog controls | Gain (0 ... 12 dB) Offset (0 ... 63 LSB 10 Bit) |
|-----------------|--|

| | |
|--------------|------|
| color models | Mono |
|--------------|------|

interfaces and connectors

| | |
|-------------------|---|
| data interface | Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Fast Ethernet, Transfer Rate 100 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), screwable type |
| process interface | M8 / 4 pins (SACC-DSI-M 8MS-4CON-L180) |
| power supply | M8 / 4 pins |

mechanical data

| | |
|------------|--|
| material | zinc die casting, nickel-plated, IP 40 |
| lens mount | CS-Mount |
| width | 29 mm |
| height | 29 mm |
| depth | 49 mm |
| weight | ≤ 120 g |

electrical data

| | |
|-------------------|-----------------------------------|
| power consumption | approx. 2,2 W @ 12 VDC and 61 fps |
|-------------------|-----------------------------------|

environmental conditions

| | |
|-----------------------|------------------------------|
| operating temperature | +5 ... +65 °C |
| humidity | 10 ... 90 % (non-condensing) |
| protection class | IP 40 |

digital I/Os

| | |
|-------|-------------------------------|
| lines | 1 input line 1 output line |
|-------|-------------------------------|

dimension drawing

