HIKVISION[°]

MV-CA013-20GM/GC 1.3 MP, 1/2" CMOS GigE Camera

- Gigabit Ethernet (1 Gbps)
- 100 m Transmit Range w/o Relaying
- 128 MB On-Board Buffer for Image Bursts
- Auto Exposure Control, LUT, Gamma Correction
- Synchronize Cameras with Hard/Soft Trigger
- Multiple Exposure Modes
- GigE Vision v1.2 Compliant


The Hikvision MV-CA013-20GM/GC 1.3 MP 1/2" CMOS GigE Camera is a high quality device that can be used in a variety of applications, including electronic semiconductor fabrication, factory automation, food and beverage inspection, and medicine package inspection.

Available Models: Mono: MV-CA013-20GM Color: MV-CA013-20GC





MV-CA013-20GM/GC Quantum Efficiency




MV-CA013-20GM/GC Quantum Efficiency



Specifications

	MV-CA013-20GM	MV-CA013-20GC
Camera		
Туре	1.3 MP; 1/2" CMOS GigE camera	
Sensor	OnSemi Python1300, 1/2" CMOS	
Shutter	Global shutter	
Resolution	1280 × 1024	
Pixel Size	4.8 μm × 4.8 μm	
Frame Rate		45 fps @ 1280 × 1024, YUV 90 fps @ 1280 × 1024, Bayer 8
Dynamic Range	>60 dB	
SNR		
Gain Range	0 to 15 dB	
Exposure Time		
	Auto-exposure, manual exposure, one-key exposure	
Network	Gigabit Ethernet	
General Purpose I/O	Opto-isolated input x 1, opto-isolated output x 1 Bi-directional non-isolated I/O x 1	
Image Buffer	128 MB	
Data Format	Mono: 8/10/10p/12/12p	Mono: 8/10/12, Bayer RG: 8/10/10p/12/12p, YUV422: 8, YUV422 (UYVY): 8, RGB: 8
General		
Power	Approximately 2.6 W @ 12 VDC, voltage: 5 to 7	15 VDC, PoE
Temperature	Working temperature: 32° to 122° F (0° to 50° C Storage temperature: -22° to 158° F (-30° to 70	^o C)
Dimensions	1.14" x 1.14" x 1.65" (29 mm × 29 mm × 42 mm	n)
Weight	Approximately 2.4 oz (68 g)	·
Lens Interface	C-mount	
Software	MVS or third-party software supporting GigE Vi	sion protocol
Operating System	Windows XP/7/8 32-/64-bit	
Compliance	GigE Vision v1.2	
Certification	CE, FCC, RoHS	

Dimensions



Recommended Accessories

• Power Adapter: 12 VDC @1 A

• NIC: Intel Pro1000 and above version

Network Cable: CAT5e or CAT6 network cable



Hikvision USA Inc., 18639 Railroad Street, City of Industry, CA 91748, USA • Hikvision Canada, 4848 rue Levy, St-Laurent, Quebec, Canada, H4R 2P1 Tel: +1-909-895-0400 • Toll Free in USA: +1-866-200-6690 • E-Mail: sales.usa@hikvision.com • www.hikvision.com © 2017 Hikvision USA Inc. • All Rights Reserved • Specifications subject to change without notice. 070617NA