

BayQad 612

Rugged 12.1" Stand-alone Data/Video Monitor for Tripod Mounting



- Rugged Data / Video Monitor
- 12.1" color TFT Flat Panel
- 800 x 600 pixels (SVGA)
- Analog RGB interface
- CVBS and S-Video inputs as option
- Milled aluminum housing

The passive cooling design of Baytek's BayQad monitors eliminates the need for ventilation openings. This design, in combination with the tough aluminum housing which is milled from solid aluminum, provides the ideal basis for all-over IP65 protection.

The chassis also has excellent shielding and dissipation characteristics. Independent test labs regularly verify the EMC (electro-magnetic compatibility) performance of BayQad monitors.

Resistance to shock and vibration and fault-free operation when the monitors are subjected to extreme temperature variations are also certified.

The BayQad monitors with internal DC/DC converters are available for mobile applications. The BayQad's comply with the VESA 100 mounting standard and can be easily attached to any stand.

A long service life and being service and maintenance free are particularly important criteria for components used in fast-paced fields such as the pharmaceutical and food industries, and can be ensured by using BayQad monitors.

Our other product families for industrial and harsh environmental applications

BayPanel

Industrial Rack Mount Monitors

BQC

Rugged Panel PCs for Tripod Mounting

BQR

Rugged Data/Video Monitors for Defense & Naval Applications

BAYTEK

Industriesysteme GmbH
Leipziger Strasse 4
D-85386 Eching

Tel: +49 89 319 011-6
Fax: +49 89 319 011-700
Email: info@baytek.de
www.baytek.de

BayQad 612 Specification

DISPLAY

310 mm (12.1") data and video flat panel display
 Active area: 246.0 mm (H) x 184.5 mm (V), Aspect ratio: 4:3 (H:V)
 Technology: a-Si TFT, active matrix
 Color resolution: 262,144 simultaneous colors, 64 gray values
 Screen resolution: 800 (H) x 600 (V) pixels
 Pixels arrangement: RGB (Red dot, Green dot, Blue dot) vertical stripe
 Dot pitch: 0.1025 mm (H) x 0.3075 mm (V), Pixel pitch: 0.3075 mm (H) x 0.3075 mm (V)
 Typical viewing angle: CR \geq 10 : 1, Horizontal: $\pm 70^\circ$ / Vertical: $\pm 60^\circ$
 Response time: Ton + Toff (10% - 90% -10%) typical 3 ms
 Brightness: typical 450 cd/m², Contrast rate: typical 800:1

SIGNAL INPUTS

BayView AVD6 DVI, analog RGB and video to 24-bit LVDS converter card
 Analog RGB input: 162.5 MHz bandwidth, up to 100 KHz H-frequency, up to 200 Hz V-frequency (UXGA 60Hz), H-Sync. (+/-), V-Sync. (+/-), Composite-Sync. on G(reen) and H-Sync.
 Standard CVBS (Composite) and S-Video (Y/C) video inputs – as option
 NTSC-M/N/4.43, PAL-M/N/B/G/H/I/D/K/L, video formats with auto-decoding function- as option
 Picture position, phase and size recognition with automatic self-adjustment capabilities (auto-phase / auto-tracking)
 Auto-scaling to max. flat panel resolution (SVGA, XGA, SXGA, UXGA, PAL, NTSC down-scaling to 800x600 pixels)
 On-Screen-Display (OSD) for user specific adjustments, like: intensity, contrast, etc.
 The setup parameters are saved in non-volatile memory
 Gamma correction tables, 8x8 bit for R, G and B each
 DB15 connector (HD DSUB) for analog RGB input (analog VGA standard connector)
 3x BNC connectors configurable as: 3x CVBS, or 1x S-Video + 1x CVBS - as option
 DB9 connector (DSUB) for Remote Control functions: Remote-OSD and Firmware updates using the RS232 port

FRONT & CHASSIS

Rear side placed OSD keypad
 Full milled aluminum housing
 Housing finish color: black RAL 9005
 VESA-100 standard stand attachment, 8x M4x8 thread holes (4x for de VESA-100 array)
 3 mm anti-reflection mineral glass pane or 3 mm Touch Screen sensor pane
 Mechanically protected connection area
 4-pin DC connector with Filter and screw lock
 AC line input: external 90 to 264 VAC 50/60 Hz universal power supply with 12 VDC output
 Dimensions (max.): 311 (w) x 234.8 (h) x 59 (d) [mm], weight: ~ 3.4 kg

CERTIFICATIONS

Conformities: IP20 (IP42 front plate / IP20 chassis), EN55011 Class A, FCC Class A, EN50081-1, EN50082-2, EN61000-4, UL1950 / EN60950 AM1, AM2, AM3

OPTIONS

DVI Interface with 26-socket Molex DVI-I connector, 2 meter DVI data cable
 Analog resistive touch screen sensor pane + touch screen controller with RS-232 interface (-T variant)
 DC-Power input: external DC-DC Converter Box with 12 VDC (10 to 16 VDC), 24 VDC (18 to 36 VDC) or 48 VDC (36 to 72 VDC) input and 12 VDC output voltage (-DC12, -DC24 or -DC48)
 Allover IP65 / NEMA4 conformity (-IP65)

